

PATENT OFFICE
JAPANESE GOVERNMENT

This is to certify that the annexed is a true copy
of the following application as filed with this Office.

Date of Application: November 28, 1997

Application Number: Japanese Patent Application
No. 9-327466

Applicant(s): CANON KABUSHIKI KAISHA

December 18, 1998

Director-General,
Patent Office TAKESHI ISAYAMA (Seal)

Certificate No. 10-3101100

9-327466

[Name of the document]	Patent Application
[Reference No.]	3510026
[Date]	November 28, 1997
[Addressed to]	Director-General of the Patent Office
[International Classification]	G06F 3/12
[Title of the Invention]	Printer Server, Method For Processing Data In Printer Server, And Storage Medium Storing Program That Can Be Read By Computer
[Number of the Claims]	14
[Inventor]	
[Domicile or Residence]	c/o Canon Kabushiki Kaisha 30-2, 3-chome, Shimomaruko, Ohta-ku, Tokyo
[Name]	TAKEYUKI NAGASHIMA
[Applicant]	
[Identification No.]	000001007
[Name]	CANON KABUSHIKI KAISHA
[Representative]	HAJIME MITARAI
[Attorney]	
[Identification No.]	100071711
[Patent Attorney]	
[Name]	MASATAKA KOBAYASHI

[Indication of Official Fee]

[Prepayment Ledger No.] 006507

[Amount] 21000

[List of Filed Materials]

[Material]	Specification	1
------------	---------------	---

[Material]	Drawings	1
------------	----------	---

[Material]	Abstract	1
------------	----------	---

[General Power of Attorney] 9703712



9-327466

[Name of the Document]	Specification
[Title of the Invention]	Printer Server, Method For Processing Data In Printer Server, And Storage Medium Storing Program That Can Be Read By Computer

[What is Claimed is]

[Claim 1]

A printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer printer data to a printer, comprising:

request means for requesting correction data for correcting said print information in accordance with a state of said printer to said print at a predetermined timing;

acquiring means for acquiring said correction data which is transferred from said printer upon request of said request means;

storing means for storing said correction data acquired by said acquiring means;

receiving means for receiving said printer information which follows a printing request from either one of said data processing devices;

discrimination means for discriminating whether or not said correction data has been already stored in said storing means at the time of reception of said print

information;

producing means for producing a correction table for correcting said print data on the basis of said correction data when said discrimination means discriminates that said correction data has been already stored in said storing means; and

correction means for correcting said print data which is produced from said print information received from either one of said data processing devices on the basis of said correction table produced by said producing means.

[Claim 2]

A printer server data processing method for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising:

a requesting step for requesting correction data for correcting said print information in accordance with a state of said printer to said printer at a predetermined timing;

an acquiring step for acquiring said correction data which is transferred from said printer upon request of said request means;

a storing step for storing said correction data acquired by said acquiring step in a memory;

a receiving step for receiving said printer information which follows a printing request from either one of said data processing devices;

a discrimination step for discriminating whether or not said correction data has been already stored in said memory at the time of reception of said print information;

a producing step for producing a correction table for correcting said print data on the basis of said correction data when it is discriminated by said discrimination step that said correction data has been already stored in said storing means; and

a correction step for correcting said print data which is produced from said print information received from either one of said data processing devices on the basis of said correction table produced by said producing step.

[Claim 3]

A storage medium storing a program which can be read by a computer for controlling a printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising:

a requesting step for requesting correction data for correcting said print information in accordance with a state of said printer to said printer at a predetermined timing;

an acquiring step for acquiring said correction data which is transferred from said printer upon request of said request means;

a storing step for storing said correction data acquired by said acquiring step in a memory;

a receiving step for receiving said printer information which follows a printing request from either one of said data processing devices;

a discrimination step for discriminating whether or not said correction data has been already stored in said memory at the time of reception of said print information;

a producing step for producing a correction table for correcting said print data on the basis of said correction data when it is discriminated by said discrimination step that said correction data has been already stored in said storing means; and

a correction step for correcting said print data which is produced from said print information received from either one of said data processing devices on the basis of said correction table produced by said producing step.

[Claim 4]

A printer server data processing method for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising:

a printer managing correction data request step for requesting correction data for effecting calibration for said printer from said sever computer;

a printer managing correction data existence discriminating step for discriminating whether or not correction data for effecting calibration is transmitted by said printer managing correction data request step as

a response to the server computer from said printer;

a printer managing correction data acquiring step for acquiring, when the correction data for effecting calibration is transmitted by said printer managing correction data existence discriminating step, said correction data;

a correction data storing step for storing said acquired correction data in a memory unit of said server computer in order to manage said correction data with said server computer;

an uncorrected print data receiving step for receiving print data which has not been corrected yet from said client computer;

a server managing correction data existence discriminating step for discriminating whether said correction data exists in said memory unit or not;

a correction table producing step for producing a correction table by acquiring the correction data for executing calibration when said correction data is discriminated to exist in the memory unit for managing the server by said server managing correction data existence discriminating step;

a correction table production discriminating step for discriminating whether said correction table has been produced or not; and

a calibration effecting step for effecting, when said correction table is discriminated to be produced by

said correction table production discriminating step, calibration for the print data by the use of the produced correction table.

[Claim 5]

A storage medium storing a program which can be read by a computer for controlling a printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising:

a printer managing correction data request step for requesting correction data for effecting calibration for said printer from said sever computer;

a printer managing correction data existence discriminating step for discriminating whether or not correction data for effecting calibration is transmitted by said printer managing correction data request step as a response to the server computer from said printer;

a printer managing correction data acquiring step for acquiring, when the correction data for effecting calibration is transmitted by said printer managing correction data existence discriminating step, said correction data;

a correction data storing step for storing said acquired correction data in a memory unit of said server computer in order to manage said correction data with said server computer;

an uncorrected print data receiving step for

receiving print data which has not been corrected yet from said client computer;

a server managing correction data existence discriminating step for discriminating whether said correction data exists in said memory unit or not;

a correction table producing step for producing a correction table by acquiring the correction data for executing calibration when said correction data is discriminated to exist in the memory unit for managing the server by said server managing correction data existence discriminating step;

a correction table production discriminating step for discriminating whether said correction table has been produced or not; and

a calibration effecting step for effecting, when said correction table is discriminated to be produced by said correction table production discriminating step, calibration for the print data by the use of the produced correction table.

[Claim 6]

A printer server for receiving a printing job from a terminal and transferring the job to an output device, comprising:

recording means for storing the correction data corresponding to the output characteristic of said output device; and

correction means for correcting said printing job

on the basis of said correction data.

[Claim 7]

The printer server according to claim 6, wherein said correction data is updated by performing two-way communication with said output device.

[Claim 8]

The printer server according to claim 7, wherein said correction data is generated when said output device executes calibration on the basis of a state parameter.

[Claim 9]

A printer-server data processing method for receiving a printing job from a terminal and transferring said printing job to an output device, comprising the step of:

correcting said printing job on the basis of the correction data corresponding to the output characteristic of said output device to be stored.

[Claim 10]

The printer-server data processing method according to claim 9, wherein said correction data is updated by performing two-way communication with said output device.

[Claim 11]

The printer-server data processing method according to claim 10, wherein said correction data is generated when said output device executes calibration on the basis of a state parameter.

[Claim 12]

A storage medium storing a program which can be read by a computer for controlling a printer server for receiving a printing job from a terminal and outputting the printing job to an output device, comprising the step of:

correcting said printing job on the basis of the correction data corresponding to the output characteristic of said output device to be stored.

[Claim 13]

The storage medium storing a program that can be read by a computer according to claim 12, wherein said correction data is updated by performing two-way communication with said output device.

[Claim 14]

The storage medium storing a program that can be read by a computer according to claim 12, wherein said correction data is generated when said output device executes calibration on the basis of a state parameter.

[Detailed Description of the Invention]

[0001]

[Field of the Industrial Utilization]

The present invention relates to a printer server for processing the print information supplied from a data processor through a predetermined communication medium and transferring print data to a printer, a method for processing the data in the printer server, and a storage medium storing a program which can be read by a computer.

[0002]

[Prior Art]

To correct the state change of a conventional printer such as the change of an output image due to the change of a condition such as temperature or humidity, or the state change or deterioration state of a visible image due to the deterioration of consumables such as a drum and toner cartridge in the case of an electrophotographic printer, calibration corresponding to the state change is performed so that the printer can output an image that meets requested density and color by correcting the print information received so as to be able to output the requested density and color even if the state change occurs.

[0003]

In the case of a printing system for converting image data into binary notation with a client computer, correction data is obtained through the calibration of a printer by using the two-way-communication function of the client computer to produce a correction table and the image data is converted into binary notation by correcting the image data.

[0004]

In the case of a shared printing system in which one printer is shared by a plurality of client computers, the above correction is asynchronously performed by the client computers.

[0005]

[Problems to be Solved by the Invention]

To locally use a printer, it is possible to realize correction corresponding to the color reproducing characteristic of a printer by obtaining correction data through calibration and correcting image data as ever.

[0006]

However, in the case of the shared printing system in which one printer is used on a network and shared by a plurality of client computers, the following problem occurs.

[0007]

In the case of the above system, a printing job obtaining correction data is not always preferentially printed. When the printing job from a certain client computer is processed before the printing job of the other client computer is processed by a printer and lots of images are formed by the printer, the color reproducibility of the printer may be greatly changed due to the formation of the images.

[0008]

That is, the correction data used for the correction provided with the print information corresponding to the printing job of a certain client computer may not correspond to the color reproducibility when the printing job is processed by a printer.

[0009]

Thus, in the case of the shared printing system in

which one printer is shared by a plurality of client computers, there is a problem that the correction corresponding to the color reproducibility when printing is executed cannot be performed by a conventional method.

[0010]

Moreover, there is a problem that the application release time is prevented from being reduced while the processing and correction for producing a correction table are performed by a client computer in accordance with correction data.

[0011]

The present invention is made to solve the above problems and its object is to provide a printer server, a printer server data processing method and a storage medium for storing a program which can be read by a computer, with which it is possible to obtain, under a printing system environment that a plurality of client computers share the printer, a printed result with an image quality having stable color reproducibility all the time even when a print job is received from any client computer, by uniformly managing correction data for correcting output characteristics of a printer in accordance with a fluctuation of the output characteristics of the printer serving as an output device.

[0012]

[Means for Solving the Problems]

According to a first aspect of the present invention,

there is provided a printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer printer data to a printer, comprising: request means for requesting correction data for correcting the print information in accordance with a state of the printer to the print at a predetermined timing; acquiring means for acquiring the correction data which is transferred from the printer upon request of the request means; storing means for storing the correction data acquired by the acquiring means; receiving means for receiving the printer information which follows a printing request from either one of the data processing devices; discrimination means for discriminating whether or not the correction data has been already stored in the storing means at the time of reception of the print information; producing means for producing a correction table for correcting the print data on the basis of the correction data when the discrimination means discriminates that the correction data has been already stored in the storing means; and correction means for correcting the print data which is produced from the print information received from either one of the data processing devices on the basis of the correction table produced by the producing means.

[0013]

According to a second aspect of the present invention, there is provided a printer server data

processing method for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising: a requesting step for requesting correction data for correcting the print information in accordance with a state of the printer to the printer at a predetermined timing; an acquiring step for acquiring the correction data which is transferred from the printer upon request of the request means; a storing step for storing the correction data acquired by the acquiring step in a memory; a receiving step for receiving the printer information which follows a printing request from either one of the data processing devices; a discrimination step for discriminating whether or not the correction data has been already stored in the memory at the time of reception of the print information; a producing step for producing a correction table for correcting the print data on the basis of the correction data when it is discriminated by the discrimination step that the correction data has been already stored in the storing means; and a correction step for correcting the print data which is produced from the print information received from either one of the data processing devices on the basis of the correction table produced by the producing step.

[0014]

According to a third aspect of the present invention, there is provided a storage medium storing a program which

can be read by a computer for controlling a printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising: a requesting step for requesting correction data for correcting the print information in accordance with a state of the printer to the printer at a predetermined timing; an acquiring step for acquiring the correction data which is transferred from the printer upon request of the request means; a storing step for storing the correction data acquired by the acquiring step in a memory; a receiving step for receiving the printer information which follows a printing request from either one of the data processing devices; a discrimination step for discriminating whether or not the correction data has been already stored in the memory at the time of reception of the print information; a producing step for producing a correction table for correcting the print data on the basis of the correction data when it is discriminated by the discrimination step that the correction data has been already stored in the storing means; and a correction step for correcting the print data which is produced from the print information received from either one of the data processing devices on the basis of the correction table produced by the producing step.

[0015]

According to a fourth aspect of the present

invention, there is provided a printer server data processing method for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising a printer managing correction data request step for requesting correction data for effecting calibration for the printer from the sever computer; a printer managing correction data existence discriminating step for discriminating whether or not correction data for effecting calibration is transmitted by the printer managing correction data request step as a response to the server computer from the printer; a printer managing correction data acquiring step for acquiring, when the correction data for effecting calibration is transmitted by the printer managing correction data existence discriminating step, the correction data; a correction data storing step for storing the acquired correction data in a memory unit of the server computer in order to manage the correction data with the server computer; an uncorrected print data receiving step for receiving print data which has not been corrected yet from the client computer; a server managing correction data existence discriminating step for discriminating whether the correction data exists in the memory unit or not; a correction table producing step for producing a correction table by acquiring the correction data for executing calibration when the correction data is discriminated to exist in the memory unit for managing the

server by the server managing correction data existence discriminating step; a correction table production discriminating step for discriminating whether the correction table has been produced or not; and a calibration effecting step for effecting, when the correction table is discriminated to be produced by the correction table production discriminating step, calibration for the print data by the use of the produced correction table.

[0016]

According to a fifth aspect of the present invention, there is provided a storage medium storing a program which can be read by a computer for controlling a printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, comprising: a printer managing correction data request step for requesting correction data for effecting calibration for the printer from the sever computer; a printer managing correction data existence discriminating step for discriminating whether or not correction data for effecting calibration is transmitted by the printer managing correction data request step as a response to the server computer from the printer; a printer managing correction data acquiring step for acquiring, when the correction data for effecting calibration is transmitted by the printer managing correction data existence discriminating step, the correction data; a correction data storing step for storing

the acquired correction data in a memory unit of the server computer in order to manage the correction data with the server computer; an uncorrected print data receiving step for receiving print data which has not been corrected yet from the client computer; a server managing correction data existence discriminating step for discriminating whether the correction data exists in the memory unit or not; a correction table producing step for producing a correction table by acquiring the correction data for executing calibration when the correction data is discriminated to exist in the memory unit for managing the server by the server managing correction data existence discriminating step; a correction table production discriminating step for discriminating whether the correction table has been produced or not; and a calibration effecting step for effecting, when the correction table is discriminated to be produced by the correction table production discriminating step, calibration for the print data by the use of the produced correction table.

[0017]

According to a sixth aspect of the present invention, there is provided a printer server for receiving a printing job from a terminal and transferring the job to an output device, comprising: recording means for storing the correction data corresponding to the output characteristic of the output device; and correction means for correcting the printing job on the basis of the correction data.

[0018]

According to a seventh aspect of the present invention, the correction data is updated by performing two-way communication with the output device.

[0019]

According to an eighth aspect of the present invention, the correction data is generated when the output device executes calibration on the basis of a state parameter.

[0020]

According to a ninth aspect of the present invention, there is provided a printer-server data processing method for receiving a printing job from a terminal and transferring the printing job to an output device, comprising the step of correcting the printing job on the basis of the correction data corresponding to the output characteristic of the output device to be stored.

[0021]

According to a tenth aspect of the present invention, the correction data is updated by performing two-way communication with the output device.

[0022]

According to an eleventh aspect of the present invention, the correction data is generated when the output device executes calibration on the basis of a state parameter.

[0023]

According to a twelfth aspect of the present invention, there is provided a storage medium storing a program which can be read by a computer for controlling a printer server for receiving a printing job from a terminal and outputting the printing job to an output device, comprising the step of correcting the printing job on the basis of the correction data corresponding to the output characteristic of the output device to be stored.

[0024]

According to a thirteenth aspect of the present invention, a program that can be read by a computer for updating the correction data is stored by the storage medium by performing two-way communication with the output device.

[0025]

According to a fourteenth aspect of the present invention, in the storage medium storing a program which can be read by a computer, the correction data is generated when the output device executes calibration on the basis of a state parameter.

[0026]

[Detailed Description of the Preferred Embodiments]

The preferred embodiments of the present invention are described below by referring to the accompanying drawings.

[0027]

FIG. 1 is a block diagram for explaining the structure of a printing system to which the printer server

of an embodiment of the present invention can be applied. The printing system is constituted with a server computer (printer server) having the two-way function, a client computer, and a printer. In the case of the printing system using this embodiment, a printer server is set between a client computer on one hand and a printer on the other. Moreover, the printer server controls the printing job supplied from each client in uniformed or distributed manner, and calibration.

[0028]

In FIG. 1, the printing system is constituted with a server computer 100, a client computer 200, a printer 300, and a communication line 400 for connecting them.

[0029]

The server computer 100 is provided with a first data control unit 101, a first calibration control unit 102, a first memory 103, a first recording-medium reading unit 104, a first input/output data control unit 105, a first interface control unit 106, a first CPU 107 for controlling every operation of the server computer 100, and a system bus 108 for connecting them. In this case, the first data control unit 101 has the function of a so-called language monitor connected with the printer in two-way manner to obtain correction data or a function equivalent to that of the monitor and moreover, has the so-called printer-server function for controlling a plurality of printing jobs. Moreover, the first data control unit 101 stores the print

data received from the client computer 100 in a medium to be read by the first memory 103 or first recording-medium reading unit 104 and controls the processing for transmitting the print data to the printer 300 in accordance with printing-job control.

[0030]

Moreover, the first recording-medium reading unit 104 and a second recording-medium reading unit 204 to be described later can read programs and image data from a storage medium such as an FD (floppy disk), CD-ROM, ROM, or magnetic tape of a language monitor or a printer driver.

[0031]

The client computer 200 is provided with a second data control unit 201, a second calibration control unit 202, a second memory 203, a second recording-medium reading unit 204, a second input/output data control unit 205, a second interface control unit 206, a display unit 207, an input device 208, a second CPU 209 for controlling every operation of the client computer 200, and a system bus 210 for connecting them.

[0032]

The display unit 207 is a display device such as a CRT display or liquid-crystal display. The input device 208 is a pointing device such as a keyboard or mouse.

[0033]

In this case, the second data control unit 202 is a so-called printer driver. The printer driver is a program

for processing print data generated through an application in accordance with a printer between an operating system resident on the client computer 200 and the printer 300 and controls the printer 300 and the program is stored in the second memory 203 or a medium to be read by the second recording-medium reading unit 204. The communication line 400 is a two-way serial interface such as a normal LAN, IEEE1394, or USB.

[0034]

The printer 300 is provided with a controller 301, a third memory 302 controlled by the controller 301 and an engine unit 303.

[0035]

The engine unit 303 particularly has a function capable of properly communicating a calibration request to the controller in addition to the normal engine-processing function.

[0036]

The controller 301 particularly has a function for executing the calibration processing when calibration is requested by the engine unit, obtaining correction data, storing the data in a third memory 302 in addition to the normal controller-processing function.

[0037]

Moreover, the engine unit 303 issues a calibration request to the controller 301 when one of various state parameters showing the states of the unit 303 reaches a

predetermined value. In the case of an electrophotographic engine, the state parameters include the operation frequency of a photosensitive drum after replaced, the temperature and humidity in a printer, and the temperature of a fixing unit for melting toner in the printer.

[0038]

Furthermore, in the case of an ink jet system for heating ink with a heater to cause film boiling and discharging the ink by the pressure, the temperature of the ink and the temperature of a heater for heating the ink serve as state parameters.

[0039]

Furthermore, the engine unit 303 monitors these parameters with various sensors or counters. Furthermore, the unit 303 has a density sensor for directly detecting the toner density on a drum. Therefore, the unit 303 can also be used for calibration by directly detecting the density of an image.

[0040]

[Structure of printer]

An example of the structure of the electrophotographic printer 300 is described below.

[0041]

The print data received from a server computer is image-processed by the controller 301 and input to the engine unit 303 in which image formation processing is performed.

[0042]

The controller 301 performs the processing for developing the print data shown by PDL (Page Description Language) already corrected into luster image data.

[0043]

The engine unit 303 forms an electrostatic latent image by scanning a photosensitive drum with a laser beam modulated in accordance with the luster image data for each developed color (C, M, Y, or K) by a polygon mirror.

[0044]

Then, the unit 303 obtains a visible image by toner-developing the electrostatic latent image and multiple-transfers the visible image to an intermediate transfer body on all colors to form a colored visible image. Moreover, the unit 303 transfers the colored visible image to a transfer material to fix the colored visible image on the transfer material. An image formation unit for performing the above control is constituted with a drum unit having a photosensitive drum, a primary electrification unit having a contact electrification roller, a cleaning unit, a development unit, an intermediate transfer body, a form-feed unit including a form cassette and various rollers, a transfer unit including a transfer roller, and a fixing unit.

[0045]

In this case, the drum unit is constituted by integrating a photosensitive drum (photosensitive body)

with a cleaner vessel having a cleaning function and also serving as the holder of the photosensitive drum. The drum unit is removably supported to the printer body and constituted so that the unit can be easily replaced in accordance with the service life of the photosensitive drum. The photosensitive drum is constituted by applying an organic photoconductor layer on the outer periphery of an aluminum cylinder and rotatably supported to the cleaner vessel. The photosensitive drum is rotated by the driving force transferred from a driving motor and the driving motor rotates the photosensitive drum counterclockwise in accordance with the image forming operation. The photosensitive drum is constituted so that an electrostatic latent image is formed by selectively exposing the surface of the photosensitive drum with a laser beam supplied from a scanner unit. In the case of the scanner unit, a modulated laser beam is reflected by a polygon mirror rotated by a motor synchronously with a horizontal-synchronizing signal for an image signal to irradiate the photosensitive drum through a lens and a reflector.

[0046]

The development unit has three color development counters for performing development of yellow (Y), magenta (M), and cyan (C) and a black development counter for performing the development of black (K) in order to change the electrostatic latent image to a visible image. The color development counter and the black development counter

are respectively provided with sleeves and a coating blade pressure-welded to the outer periphery of each sleeve. Moreover, three color development counters are respectively provided with a coating roller.

[0047]

Furthermore, the black development counter is removably set to the printer body and each color development is removably set to a development rotary about a rotation axis.

[0048]

The sleeves of the black development counter are respectively arranged with a very small interval of, for example, approximately 300 μm separate from the photosensitive drum. The black development counter carries toner with a feed member built in the counter and supplies electric charges to toner through frictional electrification so as to apply toner to the outer periphery of each sleeve rotating clockwise with a coating blade. Moreover, by applying a bias to the sleeves, the photosensitive drum is developed correspondingly to an electrostatic latent image to form a visible image of black toner on the photosensitive drum.

[0049]

Three color development counters rotate in accordance with the rotation of the development rotary to form an image and a predetermined sleeve faces the photosensitive drum at a very small interval of

approximately 300 μm from the photosensitive drum. Thereby, a predetermined color development counter stops at a development position facing the photosensitive drum and a visible image is formed on the photosensitive drum.

[0050]

To form a color image, the development rotary rotates for each turn of the intermediate transfer body and the development process is executed in order of yellow development counter, magenta development counter, cyan development counter, and black development counter, the intermediate transfer body rotates four turns to successively form visible images of yellow, magenta, cyan, and black toners, resulting in full colored visible images on the intermediate transfer body.

[0051]

The intermediate transfer body is constituted so as to rotate in accordance with the rotation of the photosensitive drum by contacting the photosensitive drum, which rotates clockwise when a color image is formed and receives the multiple transfer of four-turn visible image from the photosensitive drum. Moreover, the intermediate transfer body simultaneously multiple-transfers a colored visible image on the intermediate transfer material to a transfer material because a transfer roller to be described later contacts the intermediate transfer body when the image is formed to hold and carry the transfer body. A TOP sensor and an RS sensor for detecting a position related to the rotational direction of the intermediate transfer body and

a density sensor for detecting the density of a toner image transferred to the intermediate transfer body are arranged on the outer periphery of the intermediate transfer body. The transfer roller separates downward so as not to disturb a colored visible image while multiple-transferring the colored visible image onto the intermediate transfer body. Moreover, after four colored visible images are formed on the intermediate transfer body, the transfer roller is moved upward with a cam member in accordance with the timing for transferring the colored visible images to the transfer material. Thereby, the transfer roller is pressure-welded to the intermediate transfer body at a predetermined pressure through the transfer material, a bias voltage is applied, and the colored visible images on the intermediate transfer body are transferred to the transfer material. The fixing unit fixes the transferred colored visible images while carrying the transfer material, which is provided with a fixing roller for heating the transfer material and a pressure roller for pressure-welding the transfer material to the fixing roller. The fixing roller and the pressure roller are formed into hollow bodies and a heater is built in the rollers. That is, the transfer material holding colored visible images are carried by the fixing roller and the pressure roller and toner is fixed to the surface of the rollers by adding heat and pressure. The transfer material in which the visible images are fixed is thereafter ejected to a paper ejection unit by a paper ejection roller and the image forming operation is completed.

[0052]

Cleaning means cleans the toner left on the photosensitive drum and the intermediate transfer body and the waste toner after transferring a visible image of toner formed on the photosensitive drum to the intermediate transfer body or the waste toner after transferring the four colored visible images formed on the intermediate transfer body to the transfer material is stored in the cleaner vessel.

[0053]

FIGS. 2 to 7 are flowcharts showing an example of the data-processing procedure by a printing system using an embodiment, FIGS. 2 and 3 correspond to the data correction control procedure by the first calibration control unit 102 shown in FIG. 1, and FIG. 4 corresponds to the data correction control procedure by the second calibration control unit 202 shown in FIG. 1. Numbers (1), (2), (11) to (13), (21), and (22) respectively show each step.

[0054]

Moreover, FIG. 5 is a flowchart showing the detailed procedure of the first calibration shown in FIG. 2 and numbers (31) to (34) respectively show each step.

[0055]

The first calibration includes the printer correction data requesting step (31), printer correction data presence deciding step (32), printer control correction data obtaining step (33), and server control

correction data storing step (34).

[0056]

Moreover, FIG. 6 corresponds to the detailed procedure in the first calibration step (13) at the client side shown in FIG. 3, which includes the before-correction print data transfer accessing step (41).

[0057]

Furthermore, FIG. 7 corresponds to the detailed procedure at the server computer side shown in FIG. 4, which includes the before-correction print data receiving step (51), correction-data-obtaining memory accessing step (52), server control correction data presence deciding step (53), server control correction data obtaining step (54), correction table production deciding step (55), correction table production deciding step (56), and calibration executing step (57).

[0058]

The data correcting operation by this embodiment constituted as described above is described below by referring to FIGS. 2 to 7.

[0059]

The processing for the server computer 100 to obtain correction data in accordance with the control by the first calibration control unit 102 is described below by referring to FIGS. 2 and 5.

[0060]

It is decided whether the present is the timing for obtaining correction data (1) and the decision results in

"YES". Thereby, the first calibration at the server side (shown in FIG. 5) is executed (2).

[0061]

The timing for obtaining correction data can be executed asynchronously or synchronously with the second data control unit 201 of a client computer which is described later, as shown in the present embodiment.

[0062]

For example, for the timing to be executed asynchronously with the unit 201, there is a method of using a certain elapsed time as the obtaining timing by using a system clock or the like. Moreover, for the timing to be executed synchronously with the unit 201, there is a method of using the time when print data is transmitted from a client computer as the obtaining timing.

[0063]

The first calibration control unit 102 requests correction data for the controller 301 of the printer 300 {step (31)} to decide whether correction data is present in the third memory 302 {step (32)}. Step (32) compares, for example, the calibration execution date which is the additional information for the correction data previously stored in the first memory 103 with the calibration execution date which is the additional information for the correction data stored in the third memory 302 to decide whether the correction data stored in the first memory 103 is the latest correction data. Then, when the correction data is the latest data, step (32) completes the first

calibration of a server. Thus, by completing the first calibration in accordance with the decision result by step (32), it is possible to prevent steps (33) and (34) from being unnecessarily executed and improve the processing efficiency.

[0064]

Correction data is the data generated through the calibration performed by the engine unit 303, which is the data for correcting the change of color reproducibilities of the engine unit 303 produced due to change with time or environmental change.

[0065]

Calibration is started when the engine unit 303 of the printer 300 issues a calibration request to the controller 301 and the controller 301 returns a calibration execution command to the engine unit 303 correspondingly to the request and executed in accordance with the control by the controller 301.

[0066]

As disclosed in Japanese Patent Application Laid-open No. 7-92385 applied by the present applicant, calibration is constituted with two types of processing such as Dmax control for controlling the process of the engine unit 303 and the processing for obtaining correction data by measuring the gradation batch generated by an engine for which the Dmax control is performed every recording agent.

[0067]

Correction data is the data generated for each

recording agent and the data showing the relation between input density and actually-formed output density. Correction data is described below by referring to FIG. 8.
[0068]

FIG. 8 is an illustration showing an example of correction data corresponding to a certain recording agent, in which y-axis shows output density obtained by measuring generated gradation batch and x-axis shows input density input to an engine unit in order to generate gradation batch.
[0069]

In the case of the color reproducing characteristic of the engine unit 303, it is ideally preferable that input density and output density are matched as shown by the broken line. However, when the above-mentioned state parameter reaches a threshold, the color reproducing characteristic of the engine unit 303 is deviated from the ideal line as shown by the continuous line. Therefore, the color reproducing characteristic shown by the continuous line deviated from the ideal line is recorded by correction data. For example, the information showing a calibration date is added to output densities O1 to O5 to predetermined input densities I1 to I5 as correction data and used.
[0070]

When it is decided in step (32) shown in FIG. 5 that correction data is present, correction data is obtained from the third memory 302 through communication between the controller 301 and the first calibration control unit 102 of the first data control unit 101 {step (33)}. Then, the

obtained correction data is stored in the first memory 103 of the server computer 100 {step (34)}.

[0071]

Printing performed in accordance with a printing job is described below by referring to FIGS. 3, 4, and 6.

[0072]

In FIG. 3, when the input operation for executing printing is performed for an application or printer driver by an operator through the input device 208 and display unit 207 in the client computer 200 {step (11)}, these processings are performed asynchronously with the processing in the server computer 100.

[0073]

Normal first image processing is applied to print data (12). Moreover, the first image processing converts RGB (8 bits) data into CMYK (8 bits) data when processing, for example, print data as color data with the print data control unit 201.

[0074]

As the first image processing, for example, color matching using an input device on which print data depends and the printer 300 as an output device, brightness-density conversion for converting the RGB data to which the color matching is applied into the CMYK data, and masking UCR processing are performed.

[0075]

Moreover, as shown in FIG. 6, the print data before correction to which conversion into the CMYK (8 bits) data

is applied is transferred to the server computer 200 {step (41)}.

[0076]

For the above step (41), the processing shown in FIG. 4 is performed in the server computer 200. The processing shown in FIG. 7 is performed as the second calibration {step (21)}.

[0077]

First, the print data before correction is received {step (51)}. Then, the first memory 103 in which correction data is stored in step (2) in FIG. 2 is accessed {step (52)}, it is decided whether the correction data for performing calibration is present {step (53)}, and the decision results in "YES". Then, correction data is read out of the storage region of the first memory 103 {step (54)} and a correction table is produced {step (55)}.

[0078]

In this case, the correction table is a table for correcting the relation between input and output densities before correction shown by the continuous line to the ideal relation shown by the broken line in the case of the example shown in FIG. 8.

[0079]

In step (55), a correction curve is generated by estimating the curve shown by the continuous line in FIG. 8 showing the color reproducing characteristic of a changed engine unit in accordance with the stored correction data and converting the curve so that the curve becomes

line-symmetric to the ideal line shown by the broken line. One-dimensional LUT is generated in accordance with the correction curve. Then, the one-dimensional LUT generation is performed for each recording agent.

[0080]

Then, it is decided whether a correction table is produced in step (55) (56). The decision results in "YES" and the CMYK (8 bits) data received by using the produced correction table is corrected {step (57)}.

[0081]

Then, the second image processing is applied to print data {step (22)}. Moreover, the second image processing includes the binary-notation processing and output processing to be performed for the corrected CMYK (8 bits) data.

[0082]

Moreover, it is needless to say that the first calibration control unit 102 of the server computer 100 shown in FIG. 1 can apply proper correction then requested by a printer to print data by not correcting the print data before correction received from the client computer 200 in reentrant manner or by obtaining the correction data from a printer after processing a printing job at the timing for obtaining the correction data from the printer.

[0083]

The above procedure makes it possible to form a high-quality output image in the server computer 100 having a two-way function for the calibration request from the

printer 300. That is, it is possible to form and output a high-quality image independently of the state of the printer 300.

[0084]

[Modification]

In the case of the above embodiment, the output densities O1 to O5 to the predetermined input densities I1 to I5 shown in FIG. 8 are stored in the third memory 302 as correction data.

[0085]

A modification previously obtains the relation between input and output densities for the change of each state parameter through experiments and stores the relation in the third memory 302.

[0086]

For example, by making fixing temperature correspond to temperature T, the relation between input and output densities is obtained. Then, in the case of calibration, a controller requests the value of each state parameter for an engine unit in accordance with a calibration request, synthesizes the relation between input and output densities corresponding to each obtained state-parameter value, and obtains the correction data at the present point of time.

[0087]

This modification makes it possible to shorten the time required for calibration because it is unnecessary to form gradation batch because correction data is generated.

[0088]

Correction in accordance with the correction table which is produced on the basis of the correction data is to be conducted as a single correction step (57) in the above procedure. In this case, however, this extra step is to be added to the normal processing unpreferably. For this reason, a table which includes the correction table therein may be used as a table for data conversion processing from RGB (8 bit) data to CMYK (8 bit) data in the step (13) shown in FIG. 3 so as to conduct this conversion processing and the correction simultaneously.

[0089]

In this case, in the processing {step 55} shown in FIG. 7, a table for the data conversion from RGB (8 bit) data to CMYK (8 bit) data is to be produced in accordance with the correction data. Normally, the data conversion from RGB (8 bit) data to CMYK (8 bit) data is conducted by matrix operation and the density correction can also be conducted by matrix operation, so that it is easy to produce a conversion table from synthesis of these operations.

[0090]

It is also possible to produce a conversion table by using the correction data as a key, and not by the synthesis.

[0091]

Furthermore, for the above embodiment, a printing system is described as an example in which the printer 300 is directly connected to the network shown in FIG. 1 and

the server computer 100 is operated as the computer for controlling a printing job for the printer 300. However, it is also possible to apply the printer 300 to various computer systems by locally connecting with a certain client computer (practically, the client computer serves as a server computer) instead of directly connecting with a network or locally connecting with a certain server computer instead of directly connecting with a network.

[0092]

Furthermore, it is possible to apply the printer 300 to a printing system (system for processing the entire print data with a server computer) for executing the first image processing shown in FIG. 3 before step (21) shown in FIG. 4.

[0093]

Furthermore, it is possible to store the steps shown in FIGS. 2 to 7 in a storage medium such as an FD (floppy disk), CD-ROM, ROM, or magnetic tape and in the recording-medium reading units of the server computer 100 and client computer 200.

[0094]

Furthermore, it is possible to apply the present invention to a system constituted with a plurality of units or an apparatus constituted with one unit. Furthermore, it is needless to say that the present invention can be applied to a case in which the present invention is executed by supplying a program to a system or an apparatus.

[0095]

In this case, a storage medium storing a program related to the present invention constitutes the present invention. Moreover, by reading the program from the storage medium into a system or apparatus, the system or apparatus is operated in accordance with a predetermined method.

[0096]

Furthermore, the correction table described for this embodiment, specifically described in step (55) shown in FIG. 7 can be produced by the controller 301 of the printer 300 and stored in the third memory 302.

[0097]

In this case, the first calibration control unit 102 of the server computer 100 does not obtain correction data but a correction table from the printer 300 and controls the table. Moreover, the data {step (54)} obtained by the client computer 200 is not correction data but a correction table.

[0098]

The structure of a data-processing program which can be read by a printing system to which a printer server of the present invention can be applied is described below by referring to the memory map shown in FIG. 9.

[0099]

FIG. 9 is an illustration for explaining the memory map of a storage medium for storing various data-processing programs which can be read by a printing system to which

a printer server of the present invention can be applied.

[0100]

Though not illustrated, the information for controlling program groups stored in a storage medium such as version information or a producer is also stored and moreover, the information depending on the OS at the program reading side such as an icon for identifying and displaying a program may be stored.

[0101]

Moreover, the data subordinate to various programs is also controlled in accordance with the above directory. Furthermore, a program for installing various programs in a computer or a program for decompressing a program to be installed when it is compressed may be stored.

[0102]

The functions of this embodiment shown in FIGS. 2 to 7 can be executed by a host computer in accordance with an externally-installed program. Moreover, the present invention can be applied to a case in which an information group including a program is supplied to an output device from a storage medium such as a CD-ROM, flash memory, or FD or from an external storage medium through a network.

[0103]

As described above, it is needless to say that the object of the present invention can also be achieved by supplying a storage medium storing the program code of the software for realizing the functions of the above embodiment

to a system or an apparatus and reading the program code stored in the storage medium by the system or apparatus (or CPU or MPU).

[0104]

In this case, the program code read out of the storage medium realizes the novel function of the present invention and the storage medium storing the program code constitutes the present invention.

[0105]

A storage medium for supplying a program code can use a floppy disk, hard disk, optical disk, optical-magnetic disk, CD-ROM, CD-R, magnetic tape, nonvolatile memory card, ROM, or EEPROM.

[0106]

Moreover, it is needless to say that, by executing a program code read by a computer, cases are included in which not only the functions of the above embodiment are realized but also the OS (Operating System) working on the computer or the like performs a part or the whole of actual processing in accordance with the designation of the program code, and the functions of the above embodiment are realized by the processing.

[0107]

Furthermore, it is needless to say that a case is included in which a program code read out of a storage medium is written in a memory provided for a function extension board inserted into a computer or a function extension unit

connected to the computer and thereafter, the CPU or the like provided for the function extension board or function extension unit performs a part or the whole of actual processing in accordance with the designation by the program code, and the functions of the above embodiment are realized by the processing.

[0108]

[Effect of the Invention]

As described above, according to the first aspect of the present invention, there is provided the printer server for processing print information from a plurality of data processing devices through the predetermined communication medium to transfer printer data to a printer, comprising: the request means for requesting correction data for correcting the print information in accordance with a state of the printer to the print at a predetermined timing; the acquiring means for acquiring the correction data which is transferred from the printer upon request of the request means; the storing means for storing the correction data acquired by the acquiring means; the receiving means for receiving the printer information which follows a printing request from either one of the data processing devices; the discrimination means for discriminating whether or not the correction data has been already stored in the storing means at the time of reception of the print information; the producing means for producing a correction table for correcting the print data on the basis of the correction

data when the discrimination means discriminates that the correction data has been already stored in the storing means; and the correction means for correcting the print data which is produced from the print information received from either one of the data processing devices on the basis of the correction table produced by the producing means. As a result, it is possible to conduct the same correction on the print data which is generated from the print information following the print request from any of the data processing devices in accordance with the correction table which is produced on the basis of the correction data uniformly managed by the printer server, so as to freely construct the print processing environment which allows output of the print data from each data processing device with a stable image quality.

[0109]

According to the second and the third aspects of the present invention, there is provided the printer server data processing method for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to a printer, or the storage medium storing a program which can be read by the computer for controlling the printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to the printer, comprising: the requesting step for requesting correction

data for correcting the print information in accordance with a state of the printer to the printer at a predetermined timing; the acquiring step for acquiring the correction data which is transferred from the printer upon request of the request means; the storing step for storing the correction data acquired by the acquiring step in a memory; the receiving step for receiving the printer information which follows a printing request from either one of the data processing devices; the discrimination step for discriminating whether or not the correction data has been already stored in the memory at the time of reception of the print information; the producing step for producing a correction table for correcting the print data on the basis of the correction data when it is discriminated by the discrimination step that the correction data has been already stored in the storing means; and the correction step for correcting the print data which is produced from the print information received from either one of the data processing devices on the basis of the correction table produced by the producing step. As a result, it is possible to conduct the same correction on the print data which is generated from the print information following the print request from any of the data processing devices in accordance with the correction table which is produced on the basis of the correction data uniformly managed by the printer server, so as to freely construct the print processing environment which allows output of the print data

from each data processing device with a stable image quality.

[0110]

According to the fourth and fifth aspects of the present invention, there is provided the printer server data processing method for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to the printer, or the storage medium storing a program which can be read by the computer for controlling the printer server for processing print information from a plurality of data processing devices through a predetermined communication medium to transfer print data to the printer, comprising the printer managing correction data request step for requesting correction data for effecting calibration for the printer from the sever computer; the printer managing correction data existence discriminating step for discriminating whether or not correction data for effecting calibration is transmitted by the printer managing correction data request step as a response to the server computer from the printer; the printer managing correction data acquiring step for acquiring, when the correction data for effecting calibration is transmitted by the printer managing correction data existence discriminating step, the correction data; the correction data storing step for storing the acquired correction data in a memory unit of the server computer in order to manage

the correction data with the server computer; the uncorrected print data receiving step for receiving print data which has not been corrected yet from the client computer; the server managing correction data existence discriminating step for discriminating whether the correction data exists in the memory unit or not; the correction table producing step for producing a correction table by acquiring the correction data for executing calibration when the correction data is discriminated to exist in the memory unit for managing the server by the server managing correction data existence discriminating step; the correction table production discriminating step for discriminating whether the correction table has been produced or not; and the calibration effecting step for effecting, when the correction table is discriminated to be produced by the correction table production discriminating step, calibration for the print data by the use of the produced correction table. As a result, it is possible to conduct the same correction on the print data which is generated from the print information following the print request from any of the data processing devices in accordance with the correction table which is produced on the basis of the correction data uniformly managed by the printer server, so as to freely construct the print processing environment which allows output of the print data from each data processing device with a stable image quality.

[0111]

According to the sixth aspect of the present invention, there is provided the printer server for receiving a printing job from a terminal and transferring the job to an output device, comprising: the recording means for storing the correction data corresponding to the output characteristic of the output device; and the correction means for correcting the printing job on the basis of the correction data. As a result, since the correction processing corresponding to the output characteristics of the current output device is executed for the printing job received from a terminal, it is possible to obtain a print result with a stable image quality all the time.

[0112]

According to the seventh aspect of the present invention, the above correction data is updated by performing two-way communication with the above output device. As a result, it is possible to cope with the output characteristics of the output device quickly.

[0113]

According to the eighth aspect of the present invention, the above correction data is generated when the above output device executes calibration on the basis of a state parameter. As a result, it is possible to generate the optimal timing correction data in accordance with a fluctuation of the output characteristics of the output device.

[0114]

According to the ninth and the twelfth aspects of the present invention, there is provided the printer-server data processing method for receiving a printing job from a terminal and transferring the printing job to an output device, or the storage medium storing a program which can be read by the computer for controlling the printer server for receiving a printing job from the terminal and outputting the printing job to the output device, comprising the step of correcting the printing job on the basis of the correction data corresponding to the output characteristic of the output device to be stored. As a result, since the correction processing corresponding to the output characteristics of the current output device is executed for the printing job received from a terminal, it is possible to obtain a print result with a stable image quality all the time.

[0115]

According to the tenth and thirteenth aspects of the present invention, the above correction data is updated by performing two-way communication with the above output device. As a result, it is possible to cope with the output characteristics of the output device quickly.

[0116]

According to the eleventh and fourteenth aspects of the present invention, the correction data is generated when the output device executes calibration on the basis

of a state parameter. As a result, it is possible to generate the optimal timing correction data in accordance with a fluctuation of the output characteristics of the output device.

[0117]

Accordingly, even when the print job is received from any client computer, it is possible to obtain a print result having the image quality always with a stable reproducibility.

[Brief Description of the Drawings]

[FIGURE 1]

A block diagram for explaining the structure of a printing system to which a printer server of an embodiment of the present invention can be applied.

[FIGURE 2]

A flowchart showing an example of the data-processing procedure by the printing system using the embodiment in FIG. 1.

[FIGURE 3]

A flowchart showing an example of the data-processing procedure by the printing system using the embodiment in FIG. 1.

[FIGURE 4]

A flowchart showing an example of the data-processing procedure by the printing system using the embodiment in FIG. 1.

[FIGURE 5]

A flowchart showing an example of the data-processing procedure by the printing system using the embodiment in FIG. 1.

[FIGURE 6]

A flowchart showing an example of the data-processing procedure by the printing system using the embodiment in FIG. 1.

[FIGURE 7]

A flowchart showing an example of the data-processing procedure by the printing system using the embodiment in FIG. 1.

[FIGURE 8]

An illustration showing an example of the correction data corresponding to a certain recording agent.

[FIGURE 9]

An illustration for explaining a memory map of a storage medium for storing various types of data-processing programs which can be read by a printing system to which a printer server of the present invention can be applied.

[Description of Reference Numerals or Symbols]

- 100 ... server computer
- 101 ... first data control unit
- 102 ... first calibration control unit
- 103 ... first memory
- 107 ... first CPU
- 200 ... client computer
- 201 ... second data control unit

202 ... second calibration control unit

300 ... printer

301 ... controller

302 ... third memory

[Name of the Document]

Abstract

[Abstract]

An object of the present invention is to obtain a print result of the image quality in which the color reproducibility is always stable even if receiving a printing job from any client computer.


[Means for Achieving the Object]

A first calibration control unit 102 obtains correction data from a printer 300 to store the data in a first memory 103, receives normal print information from a client computer 200, and corrects print data by referring to a correction table produced in accordance with the correction data when generating the print data based on the received print information.


[Elected Drawing]

FIGURE 1

【図2】 Fig. 2




【図3】 Fig. 3




【書類名】 図面 [name of the Document] Drawings


【図 1】 Fig. 1




【図4】 Fig. 4




【図5】 Fig. 5




【図6】 Fig. 6



【図7】 Fig. 7



【図 8】 Fig. 8



【図9】 Fig. 9

Recording medium such as FD/CD-ROM
FD/CD-ROM等の記憶媒体

ディレクトリ情報 Directory information	
第1のデータ処理プログラム 図2に示すフローチャートのステップに対応する プログラムコード群	First data processing program Program codes corresponding to step of flow chart in Fig. 2
第2のデータ処理プログラム 図3に示すフローチャートのステップに対応する プログラムコード群	Second data processing program Program codes corresponding to step of flow chart in Fig. 3
第3のデータ処理プログラム 図4に示すフローチャートのステップに対応する プログラムコード群	Third data processing program Program codes corresponding to step of flow chart in Fig. 4
第4のデータ処理プログラム 図5に示すフローチャートのステップに対応する プログラムコード群	Fourth data processing program Program codes corresponding to step of flow chart in Fig. 5
第5のデータ処理プログラム 図6に示すフローチャートのステップに対応する プログラムコード群	Fifth data processing program Program codes corresponding to step of flow chart in Fig. 6
第6のデータ処理プログラム 図7に示すフローチャートのステップに対応する プログラムコード群	Sixth data processing program Program codes corresponding to step of flow chart in Fig. 7

記憶媒体のメモリマップ

Memory map of recording medium